W9602XXXX version: 10/2018




Protective well ventilated helmet for work at heights and rescue purposes. Suitable for heavily physically working persons. Its main purpose is to protect the user against falling objects. Helmet has a solid chin strap that will withstand a load of at least 50 kg, which prevents the possibility of dropping the helmet in case of fall.

## **DESCRIPTION**





The helmet construction without EPS which provides well fitting to any head and superb durability.



W9602RX00 RED


two side and two rear adjusting sleeves to regulate the length of the chin straps



side universal 30 mm slots for hearing protection: Peltor, Hellberg, 3M...




thin profile buckle fits well with all hearing protectors



fast, easy and effective size adjustment mechanism on the back of the helmet



four head lamp holders for any head lamp available on the market



reflective stickers included



Side impact force protection according EN 12492

# **STANDARDS**

Combine requirements EN 397 and EN 12492





min. 50 kg







-10 °C







EN 397 EN 12492



**FEATURES** 

455 g 16.05 oz



53-63cm




unique number



W9602XXXX version: 10/2018

#### **MATERIALS**





## COMPATIBILITY WITH SHIELDS



Singing Rock COVER visor



Hellberg Safe 2 flex carrier

+
Steel or Nylon mesh visor
or
Polycarbonate electric visor

# **RELATED PRODUCTS**

HELMET TYPE	COLORS	STANDARDS				<b>→</b>		EN 397 EN 12492
FLASH Access		<b>C €</b> 1015	min. 50 kg	440 √ a. c.	-30°C	<	$\bowtie$	
FLASH Industry		EN 397 <b>C €</b> 1015	min. 15 kg max. 25 kg	440 √ a. c.	-30 °C		$\bowtie$	

### **MAINTENANCE**

Lifetime of this product depends on the frequency and the environment in which is used. Without taking wear or mechanical damage into account and in compliance with the conditions specified in the instructions for use this product may be used 10 years from the date of production.









UV





chemicals

read instruction

However mechanical damage can occur during the first use, which can limit the lifetime of this products only to its first use.



